

06-09-00

EE318062105 US  
June 8, 2000

## IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

Docket No. AUS990938US1

Assistant Commissioner for Patents  
Washington, D.C. 20231JC828 U.S. PTO  
09/589661  
06/08/00

Sir:

Transmitted herewith for filing is the patent application of Inventor(s):

**RICHARD LOUIS ARNDT**For: **HYPERVERSOR VIRTUALIZATION OF OS CONSOLE AND OPERATOR  
PANEL**

Enclosed are also:

- ☒ 20 Pages of Specification including an Abstract  
☒ 6 Pages of Claims  
☒ 9 Sheet(s) of Drawings  
☒ A Declaration and Power of Attorney  
☒ Form PTO 1595 and assignment of the invention to IBM Corporation

**CLAIMS AS FILED**

FOR	Number Filed		Number Extra		Rate		Basic Fee (\$690)
Total Claims	24	-20 =	4	X	\$ 18	=	\$ 72.00
Independent Claims	5	-3 =	2	X	\$ 78	=	\$ 156.00
Multiple Dependent Claims	0			X	\$260	=	\$ 0.00
<b>Total Filing Fee</b>							<b>= \$ 918.00</b>

- ☒ Please charge \$918.00 to IBM Corporation, Deposit Account No. 09-0447.  
☒ The Commissioner is hereby authorized to charge payment of the following fees associated with the communication or credit any over payment to IBM Corporation, Deposit Account No. 09-0447. A duplicate copy of this sheet is enclosed.  
☒ Any additional filing fees required under 37CFR § 1.16.  
☒ Any patent application processing fees under 37CFR § 1.17.

Respectfully,

Mark E. McBurney

Reg. No. 33,114

Intellectual Property Law Dept.

IBM Corporation

11400 Burnet Road 4054

Austin, Texas 75758

Telephone: (512) 823-1003

Docket No. AUS990938US1

## **HYPERVISOR VIRTUALIZATION OF OS CONSOLE AND OPERATOR PANEL**

### **BACKGROUND OF THE INVENTION**

5

#### **1. Technical Field:**

The present invention relates generally to the field of computer architecture and, more specifically, to methods and systems for allowing multiple operating system images within a logically partitioned data processing system to interact with a console and operator panel.

10

#### **2. Description of Related Art:**

A logical partitioning option (LPAR) within a data processing system allows multiple copies of a single operating system (OS) or multiple heterogeneous operating systems to be simultaneously run on a single data processing system platform. A partition, within which an operating system image runs, is assigned a non-overlapping sub-set of the platform's resources. These platform allocable resources include one or more architecturally distinct processors with their interrupt management area, regions of system memory, and I/O adapter bus slots. The partition's resources are represented by its own open firmware device tree to the OS image.

15

20

25

30

Each distinct OS or image of an OS running within the platform are protected from each other such that software errors on one logical partition cannot affect the correct operation of any of the other partitions.

Docket No. AUS990938US1

This is provided by allocating a disjoint set of platform resources to be directly managed by each OS image and by providing mechanisms for ensuring that the various images cannot control any resources that have not been allocated to it. Furthermore, software errors in the control of an OS's allocated resources are prevented from affecting the resources of any other image. Thus, each image of the OS (or each different OS) directly controls a distinct set of allocable resources within the platform.

10       There are certain resources within many server platforms that exist singly, yet each distinct OS within the platform must interact with these resources. For example, the RS/6000, a product of International Business Machines Corporation of Armonk, New York, includes a console and an operator panel for allowing a system administrator to detect and correct problems within the platform. However, each of these resources exists singly within the platform and it is impractical to duplicate these resources. While present architectures often do not preclude the sharing of allocable resources of this type between partitions, there is no current architectural support for such sharing. Therefore, a method, system, and computer program product for providing the sharing of allocable resources within a logically partitioned platform is desirable.

Docket No. AUS990938US1

## SUMMARY OF THE INVENTION

5           The present invention provides a logically partitioned data processing system in which shared resources are emulated to provide each partition a separate copy of the shared resource. In one embodiment, the logically partitioned data processing system includes a plurality of logical partitions, a plurality of operating systems executing within the data processing system and a plurality of assignable resources. Each of the plurality of operating systems is assigned to a separate one of the plurality of logical partitions, such that no more than one operating system is assigned to any given logical partition. Each of the plurality of assignable resources is assigned to a single one of the plurality of logical partitions. The logically partitioned data processing system also includes a hypervisor. The hypervisor emulates shared resources, such as an operator panel and a system console, and provides a virtual copy of these shared resources to each of the plurality of logical partitions.

Docket No. AUS990938US1

### BRIEF DESCRIPTION OF THE DRAWINGS

5       The novel features believed characteristic of the invention are set forth in the appended claims. The invention itself, however, as well as a preferred mode of use, further objectives and advantages thereof, will best be understood by reference to the following detailed  
10 description of an illustrative embodiment when read in conjunction with the accompanying drawings, wherein:

**Figure 1** depicts a pictorial representation of a distributed data processing system in which the present invention may be implemented;

15       **Figure 2**, a block diagram of a data processing system in accordance with the present invention is illustrated;

**Figure 3** depicts a block diagram of a data processing system, which may be implemented as a  
20 logically partitioned server, in accordance with the present invention;

**Figure 4** depicts a block diagram illustrating a prior art logically partitioned platform in accordance with the present invention;

25       **Figure 5** depicts a block diagram of a logically partitioned platform in which the present invention may be implemented;

**Figures 6A-6B** depict high-level flowcharts illustrating exemplary processes, performed for example,  
30 in hypervisor **510**, for emulating a console and operator platform in accordance with the present invention;

5

**Figure 8** depicts a high level flowchart illustrating an exemplary process on a hardware system console for sending messages to various ones of multiple OS images running on a logically partitioned platform in accordance with the present invention.

10

Docket No. AUS990938US1

#### DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENT

5           With reference now to the figures, and in particular with reference to **Figure 1**, a pictorial representation of a distributed data processing system is depicted in which the present invention may be implemented.

10           Distributed data processing system **100** is a network of computers in which the present invention may be implemented. Distributed data processing system **100** contains network **102**, which is the medium used to provide communications links between various devices and computers connected within distributed data processing  
15           system **100**. Network **102** may include permanent connections, such as wire or fiber optic cables, or temporary connections made through telephone connections.

20           In the depicted example, server **104** is connected to hardware system console **150**. Server **104** is also connected to network **102**, along with storage unit **106**. In addition, clients **108**, **110** and **112** are also connected to network **102**. These clients, **108**, **110** and **112**, may be, for example, personal computers or network computers. For purposes of this application, a network computer is  
25           any computer coupled to a network that receives a program or other application from another computer coupled to the network. In the depicted example, server **104** is a logically partitioned platform and provides data, such as boot files, operating system images and applications, to  
30           clients **108-112**. Hardware system console **150** may be a laptop computer and is used to display messages to an

00539661-000000

Docket No. AUS990938US1

operator from each operating system image running on  
server **104**, as well as to send input information,  
received from the operator, to server **104**. Clients **108**,  
**110** and **112** are clients to server **104**. Distributed data  
5 processing system **100** may include additional servers,  
clients, and other devices not shown. Distributed data  
processing system **100** also includes printers **114**, **116** and  
**118**. A client, such as client **110**, may print directly to  
printer **114**. Clients such as client **108** and client **112**  
10 do not have directly attached printers. These clients  
may print to printer **116**, which is attached to server  
**104**, or to printer **118**, which is a network printer that  
does not require connection to a computer for printing  
documents. Client **110**, alternatively, may print to  
15 printer **116** or printer **118**, depending on the printer type  
and the document requirements.

In the depicted example, distributed data processing  
system **100** is the Internet, with network **102** representing  
a worldwide collection of networks and gateways that use  
20 the TCP/IP suite of protocols to communicate with one  
another. At the heart of the Internet is a backbone of  
high-speed data communication lines between major nodes  
or host computers consisting of thousands of commercial,  
government, education, and other computer systems that  
25 route data and messages. Of course, distributed data  
processing system **100** also may be implemented as a number  
of different types of networks such as, for example, an  
intranet or a local area network.

**Figure 1** is intended as an example and not as an  
30 architectural limitation for the processes of the present



Docket No. AUS990938US1

invention.

With reference now to **Figure 2**, a block diagram of a data processing system in accordance with the present invention is illustrated. Data processing system **200** is an example of a hardware system console, such as hardware system console **150** depicted in **Figure 1**. Data processing system **200** employs a peripheral component interconnect (PCI) local bus architecture. Although the depicted example employs a PCI bus, other bus architectures, such as Micro Channel and ISA, may be used. Processor **202** and main memory **204** are connected to PCI local bus **206** through PCI bridge **208**. PCI bridge **208** may also include an integrated memory controller and cache memory for processor **202**. Additional connections to PCI local bus **206** may be made through direct component interconnection or through add-in boards. In the depicted example, local area network (LAN) adapter **210**, SCSI host bus adapter **212**, and expansion bus interface **214** are connected to PCI local bus **206** by a direct component connection. In contrast, audio adapter **216**, graphics adapter **218**, and audio/video adapter (A/V) **219** are connected to PCI local bus **206** by add-in boards inserted into expansion slots. Expansion bus interface **214** provides a connection for a keyboard and mouse adapter **220**, modem **222**, and additional memory **224**. In the depicted example, SCSI host bus adapter **212** provides a connection for hard disk drive **226**, tape drive **228**, CD-ROM drive **230**, and digital video disc read only memory drive (DVD-ROM) **232**. Typical PCI local bus implementations will support three or four PCI expansion slots or add-in connectors.

An operating system runs on processor **202** and is used to coordinate and provide control of various components within data processing system **200** in **Figure 2**. The operating system may be a commercially available operating system, such as OS/2, which is available from International Business Machines Corporation. "OS/2" is a trademark of International Business Machines Corporation. An object-oriented programming system, such as Java, may run in conjunction with the operating system, providing calls to the operating system from Java programs or applications executing on data processing system **200**. Instructions for the operating system, the object-oriented operating system, and applications or programs are located on a storage device, such as hard disk drive **226**, and may be loaded into main memory **204** for execution by processor **202**.

With reference now to **Figure 3**, a block diagram of a data processing system, which may be implemented as a logically partitioned server, such as server **104** in **Figure 1**, is depicted in accordance with the present invention. Data processing system **300** may be a symmetric

Docket No. AUS990938US1

multiprocessor (SMP) system including a plurality of processors **301**, **302**, **303**, and **304** connected to system bus **306**. For example, data processing system **300** may be an IBM RS/6000, a product of International Business Machines Corporation in Armonk, New York. Alternatively, a single processor system may be employed. Also connected to system bus **306** is memory controller/cache **308**, which provides an interface to a plurality of local memories **360-363**. I/O bus bridge **310** is connected to system bus **306** and provides an interface to I/O bus **312**. Memory controller/cache **308** and I/O bus bridge **310** may be integrated as depicted.

Data processing system **300** is a logically partitioned data processing system. Thus, data processing system **300** may have multiple heterogeneous operating systems (or multiple instances of a single operating system) running simultaneously. Each of these multiple operating systems may have any number of software programs executing within in it. Data processing system **300** is logically partitioned such that different I/O adapters **320-321**, **328-329**, **336-337**, and **346-347** may be assigned to different logical partitions.

Thus, for example, suppose data processing system **300** is divided into three logical partitions, P1, P2, and P3. Each of I/O adapters **320-321**, **328-329**, and **336-337**, each of processors **301-304**, and each of local memories **360-364** is assigned to one of the three partitions. For example, processor **301**, memory **360**, and I/O adapters **320**, **328**, and **329** may be assigned to logical partition P1; processors **302-303**, memory **361**, and I/O adapters **321** and

Docket No. AUS990938US1

**337** may be assigned to partition P2; and processor **304**, memories **362-363**, and I/O adapters **336** and **346-347** may be assigned to logical partition P3.

Each operating system executing within data processing system **300** is assigned to a different logical partition. Thus, each operating system executing within data processing system **300** may access only those I/O units that are within its logical partition. Thus, for example, one instance of the Advanced Interactive Executive (AIX) operating system may be executing within partition P1, a second instance (image) of the AIX operating system may be executing within partition P2, and a Windows 2000™ operating system may be operating within logical partition P1. Windows 2000 is a product and trademark of Microsoft Corporation of Redmond, Washington.

Peripheral component interconnect (PCI) Host bridge **314** connected to I/O bus **312** provides an interface to PCI local bus **315**. A number of Terminal Bridges **316-317** may be connected to PCI bus **315**. Typical PCI bus implementations will support four Terminal Bridges for providing expansion slots or add-in connectors. Each of Terminal Bridges **316-317** is connected to a PCI/I/O Adapter **320-321** through a PCI Bus **318-319**. Each I/O Adapter **320-321** provides an interface between data processing system **300** and input/output devices such as, for example, other network computers, which are clients to server **300**. Only a single I/O adapter **320-321** may be connected to each terminal bridge **316-317**. Each of terminal bridges **316-317** is configured to prevent the

Docket No. AUS990938US1

propagation of errors up into the PCI Host Bridge **314** and into higher levels of data processing system **300**. By doing so, an error received by any of terminal bridges **316-317** is isolated from the shared buses **315** and **312** of the other I/O adapters **321**, **328-329**, and **336-337** that may be in different partitions. Therefore, an error occurring within an I/O device in one partition is not "seen" by the operating system of another partition. Thus, the integrity of the operating system in one partition is not effected by an error occurring in another logical partition. Without such isolation of errors, an error occurring within an I/O device of one partition may cause the operating systems or application programs of another partition to cease to operate or to cease to operate correctly.

Additional PCI host bridges **322**, **330**, and **340** provide interfaces for additional PCI buses **323**, **331**, and **341**. Each of additional PCI buses **323**, **331**, and **341** are connected to a plurality of terminal bridges **324-325**, **332-333**, and **342-343** which are each connected to a PCI I/O adapter **328-329**, **336-337**, and **346-347** by a PCI bus **326-327**, **334-335**, and **344-345**. Thus, additional I/O devices, such as, for example, modems or network adapters may be supported through each of PCI I/O adapters **328-329**, **336-337**, and **346-347**. In this manner, server **300** allows connections to multiple network computers. A memory mapped graphics adapter **348** and hard disk **350** may also be connected to I/O bus **312** as depicted, either directly or indirectly. Hard disk **350** may be logically partitioned between various partitions without the need

Docket No. AUS990938US1

for additional hard disks. However, additional hard disks may be utilized if desired.

Those of ordinary skill in the art will appreciate that the hardware depicted in **Figure 3** may vary. For example, other peripheral devices, such as optical disk drives and the like, also may be used in addition to or in place of the hardware depicted. The depicted example is not meant to imply architectural limitations with respect to the present invention.

With reference now to **Figure 4**, a block diagram illustrating a prior art logically partitioned platform is depicted in accordance with the present invention. Logically partitioned platform **400** is an example of a platform that, in prior art systems, may have been implemented as server **104** in **Figure 1**. Logically partitioned platform **400** includes partitioned hardware **430**, shared single hardware **420**, and operating systems **402-408**. Operating systems **402-408** may be multiple copies of a single operating system or multiple heterogeneous operating systems simultaneously run on platform **400**.

Partitioned hardware **430** includes a plurality of processors **432-438**, a plurality of system memory units **440-446**, a plurality of input/output (I/O) adapters **448-462**, and a storage unit **470**. Each of the processors **442-448**, memory units **440-446**, and I/O adapters **448-462** may be assigned to one of multiple partitions within logically partitioned platform **400**, each of which corresponds to one of operating systems **402-408**.

Shared single hardware unit **420** includes console **422**

Docket No. AUS990938US1

and operator panel **424**. Shared single hardware unit **420** may also include other shared devices not depicted in **Figure 4**. Console **422** typically includes a display and data entry device such as a keyboard. Console **422** allows an operator to respond to and correct errors displayed on operator panel **424**. Operator panel **424** is typically a panel display, such as an LCD display, on the front of the physical chassis of the server in which text messages are displayed alerting an operator of potential problems within platform **400** or within a particular OS **402-408** running on platform **400**.

Each operating system image **402-408** must share access to resources within shared single hardware **420**. Therefore, some of the benefits of a logically partitioned platform are lost, since each partition may access and change the contents of shared resources, thus affecting other partitions within the platform. One alternative to allowing each partition to share access to shared single hardware **420** is to duplicate these hardware devices and have a separate operator panel and console for each partition. However, such a solution is bulky and, often cost prohibitive.

With reference now to **Figure 5**, a block diagram of an exemplary logically partitioned platform is depicted in which the present invention may be implemented. The hardware in logically partitioned platform **500** may be implemented as, for example, server **200** in **Figure 2**. Logically partitioned platform **500** is similar to logically partitioned platform **400** in **Figure 4**. However, Hypervisor **510**, implemented as firmware, has been added.

Docket No. AUS990938US1

Firmware is "hard software" stored in a memory chip that holds its content without electrical power, such as, for example, read-only memory (ROM), programmable ROM (PROM), erasable programmable ROM (EPROM), electrically erasable programmable ROM (EEPROM), and non-volatile random access memory (non-volatile RAM).

Hypervisor **510** provides the OS images **402-408** running in multiple logical partitions each a virtual copy of a console and operator panel. The interface to the console is changed from an asynchronous teletype port device driver, as in the prior art, to a set of hypervisor firmware calls that emulate a port device driver. The hypervisor **510** encapsulates the data from the various OS images onto a message stream that is transferred to a computer **580**, known as a hardware system console **580**.

Hardware system console **580** is connected directly to logically partitioned platform **500** as illustrated in **Figure 5**, or may be connected to logically partitioned platform through a network, such as, for example, network **102** in **Figure 1**. Hardware system console **580** may be, for example, a desktop or laptop computer, and may be implemented as data processing system **200** in **Figure 2**. Hardware system console **580** decodes the message stream and displays the information from the various OS images **402-408** in separate windows, at least one per OS image. Similarly, keyboard input information from the operator is packaged by the hardware system console, sent to logically partitioned platform **500** where it is decoded and delivered to the appropriate OS image via the hypervisor **510** emulated port device driver associated



Docket No. AUS990938US1

with the then active window on the hardware system console **580**.

Those of ordinary skill in the art will appreciate that the hardware and software depicted in **Figure 5** may vary. For example, more or fewer processors and/or more or fewer operating system images may be used than those depicted in **Figure 5**. The depicted example is not meant to imply architectural limitations with respect to the present invention.

With reference now to **Figures 6A-6B**, high-level flowcharts illustrating exemplary processes, performed for example, in hypervisor **510**, for emulating a console and operator platform is depicted in accordance with the present invention. The operating systems, such as, for example, OS **402-408** in **Figure 4**, call the hypervisor through a single entry point. One thread of execution illustrated in **Figure 6A** gets data from a per partition buffer and sends data to the hardware system console while a separate thread of execution illustrated in **Figure 6B** receives data from the hardware system console.

In the first thread of execution depicted in **Figure 6A**, the hypervisor receives a request from an operating system to get or send data (step **601**). The hypervisor determines whether the request is a request to send or get data (step **602**). If the request is a request to send data, then the hypervisor determines from which OS image (partition) the received data originated (step **604**). The received data is then encapsulated onto a message stream (step **606**). The encapsulated data includes the message or information received from the OS as well as the

Docket No. AUS990938US1

identity of the OS. The hypervisor then sends the message stream to the hardware system console (step **608**).

If the request is a request to get data, then the hypervisor determines which OS partition requested the data (step **610**). Each partition is assigned a data buffer for storing data received from the hardware system console until retrieved by the partition's OS. Thus, the hypervisor determines whether the requesting partition's data buffer is empty (step **612**). If the data buffers for the requesting partition is empty, then the hypervisor sends a NULL message to the requesting OS image indicating that there is no data from the hardware system console for the OS image to receive (step **616**). If the data buffer is not empty, then the message data from the partition's data buffer is sent to the requesting OS image (step **614**).

In the second thread of execution depicted in **Figure 6B**, the hypervisor receives and decodes data from the hardware system console (step **618**). The hypervisor then places the decoded data into the buffer corresponding to the appropriate partition such that it may be retrieved and sent to the appropriate partition's OS image upon request (step **620**).

With reference now to **Figure 7**, a high level flowchart illustrating an exemplary process on a hardware system console for presenting the information from the various OS images to an operator is depicted in accordance with the present invention. To begin, the hardware system console receives a message stream from the hypervisor (step **702**). The hardware system console decodes the message stream (step **704**) and determines to

Docket No. AUS990938US1

which OS image the received data corresponds (step **706**).  
Next, the hardware system console determines which window  
within the display corresponds to the determined OS image  
(step **708**) and displays the received data to an operator  
5 in the window corresponding to the proper OS image (step  
**710**).

With reference now to **Figure 8**, a high level  
flowchart illustrating an exemplary process on a hardware  
system console for sending messages to various ones of  
10 multiple OS images running on a logically partitioned  
platform is depicted in accordance with the present  
invention. To begin, the hardware system console  
receives input from an operator from an input device,  
such as, for example, a keyboard (step **802**). The  
15 hardware system console then determines which OS image  
corresponds to the active window from which the input was  
received (step **804**). The data input, along with the OS  
image it corresponds with, are encapsulated into a  
message stream (step **806**). The message stream is then  
20 sent to the hypervisor (step **808**).

It is important to note that while the present  
invention has been described in the context of a fully  
functioning data processing system, those of ordinary  
skill in the art will appreciate that the processes of  
25 the present invention are capable of being distributed in  
the form of a computer readable medium of instructions  
and a variety of forms and that the present invention  
applies equally regardless of the particular type of  
signal bearing media actually used to carry out the  
30 distribution. Examples of computer readable media  
include recordable-type media such as a floppy disc, a

2025 RELEASE UNDER E.O. 14176

Docket No. AUS990938US1

hard disk drive, a RAM, and CD-ROMs and transmission-type media such as digital and analog communications links.

The description of the present invention has been presented for purposes of illustration and description,  
5 but is not intended to be exhaustive or limited to the invention in the form disclosed. Many modifications and variations will be apparent to those of ordinary skill in the art. The embodiment was chosen and described in order to best explain the principles of the invention,  
10 the practical application, and to enable others of ordinary skill in the art to understand the invention for various embodiments with various modifications as are suited to the particular use contemplated.

09539621-00000000

Docket No. AUS990938US1

**CLAIMS:**

5 What is claimed is:

1. A logically partitioned data processing system, comprising:

a plurality of logical partitions;

10        a plurality of operating systems, each assigned to a  
separate one of the plurality of logical partitions;

a plurality of assignable resources, wherein each of the plurality of assignable resources is assigned to one of the plurality of logical partitions;

15        a hypervisor, wherein the hypervisor emulates shared  
resources and provides a virtual copy of the shared  
resources to each of the plurality of logical partitions.

2. The logically partitioned data processing system as  
20 recited in claim 1, wherein the shared resources comprise  
an operator panel.

3. The logically partitioned data processing system as  
recited in claim 1, wherein the shared resources comprise  
25 a system console.

4. The logically partitioned data processing system as recited in claim 1, wherein the hypervisor receives a system message from one of the plurality of operating system images, appends an operating system identity to the message to produce a new message, and sends the new

Docket No. AUS990938US1

message to an external data processing system.

5. The logically partitioned data processing system as recited in claim 1, wherein instructions for executing the hypervisor are contained within firmware.

6. The logically partitioned data processing system as recited in claim 5, wherein the firmware comprises a read-only memory.

10

7. The logically partitioned data processing system as recited in claim 5, wherein the firmware comprises a programmable read-only memory.

15 8. The logically partitioned data processing system as  
recited in claim 5, wherein the firmware comprises an  
erasable programmable read-only memory.

9. The logically partitioned data processing system as  
20 recited in claim 5, wherein the firmware comprises an  
electrically erasable programmable read-only memory.

10. The logically partitioned data processing system as  
recited in claim 5, wherein the firmware comprises a  
25 non-volatile random access memory.

11. A method of providing separate copies of shared resources to each of multiple partitions within a data processing system, the method comprising:

30       receiving, at a hypervisor, a message from a one of a plurality of operating system images, executing within

the data processing system, intended for a shared resource;

```
5      encoding the message and the identity into a new
      message; and
```

10 12. The method as recited in claim 11, wherein the  
shared resource is an operator panel.

15

```

        receiving external data from the external data
processing system;

```

transmitting the input to the intended one of the plurality of operating system images with an indication the identity of the shared resource from which the input corresponds.

15. A computer program product for providing separate  
copies of shared resources to each of multiple partitions  
30 within a data processing system, the computer program  
product comprising:

Docket No. AUS990938US1

first instructions for receiving, at a hypervisor, a message from a one of a plurality of operating system images, executing within the data processing system, intended for a shared resource;

5 second instructions for determining an identity of the one of the plurality of operating system images;

third instructions for encoding the message and the identity into a new message; and

fourth instructions for transmitting the new message  
10 to an external data processing system for presentation to a user.

16. The computer program product as recited in claim 15, wherein the shared resource is an operator panel.

15 17. The computer program product as recited in claim 15, wherein the shared resource is a system console.

18. The computer program product as recited in claim 15,  
20 further comprising:

fifth instructions for receiving external data from the external data processing system;

sixth instructions for decoding the external data to determine an input, an identity of the shared resource,  
25 and an intended one of the plurality of operating system images; and

seventh instructions for transmitting the input to the intended one of the plurality of operating system images with an indication the identity of the shared  
30 resource from which the input corresponds.

0952563-060300



19. A system for providing separate copies of shared resources to each of multiple partitions within a data processing system, the system comprising:

second means for determining an identity of the one of the plurality of operating system images;

fourth means for transmitting the new message to an external data processing system for presentation to a user.

21. The system as recited in claim 19, wherein the shared resource is a system console.

fifth means for receiving external data from the external data processing system;

seventh means for transmitting the input to the intended one of the plurality of operating system images with an

Docket No. AUS990938US1

indication the identity of the shared resource from which the input corresponds.


23. A system for partitioning shared resources, the  
5 system comprising:  
    a first data processing system comprising:  
        a plurality of partitions each corresponding to  
        separate one of a plurality of operating system  
        images;  
10       a plurality of assignable resources; and  
        a hypervisor for providing each partition a  
        separate one of a shared system resource;  
        a second data processing system coupled to the first  
data processing system, wherein the second data  
15 processing system receives a message from the hypervisor,  
wherein the message indicates to which of the plurality  
of operating system images the message belong, and  
wherein the second data processing system displays the  
message to a user with an indication of the operating  
20 system image corresponding to the message.

24. The system as recited in claim 23, wherein the data  
processing system, responsive to operator input for a  
specified one of the plurality of operating system  
25 images, sends encapsulated data, comprising the operator  
input and an indication of the corresponding operating  
system image, to the hypervisor, and wherein the  
hypervisor decodes the encapsulated data and sends the  
operator input to the corresponding operating system  
30 image.

5


# HYPERVISOR VIRTUALIZATION OF OS CONSOLE AND OPERATOR PANEL

A logically partitioned data processing system in which shared resources are emulated to provide each partition a separate copy of the shared resource is provided. In one embodiment, the logically partitioned data processing system includes a plurality of logical partitions, a plurality of operating systems executing within the data processing system and a plurality of assignable resources. Each of the plurality of operating systems is assigned to a separate one of the plurality of logical partitions, such that no more than one operating system is assigned to any given logical partition. Each of the plurality of assignable resources is assigned to a single one of the plurality of logical partitions. The logically partitioned data processing system also includes a hypervisor. The hypervisor emulates shared resources, such as an operator panel and a system console, and provides a virtual copy of these shared resources to each of the plurality of logical partitions.




100  
Network  
**Figure 1**

AUS990938US1




200  
Client  
**Figure 2**

AUS990938US1



**Figure 3**

AUS990938US1



(Prior Art)

**Figure 4**

AUS990938US1

US 2010/0199999 A1




Figure 5

AUS990938US1





Start

Decode data from hardware system  
console.  
618

Place decoded data in buffer for  
appropriate partition.  
620

Stop

Figure 6B

AUS990938US1




Figure 7

AUS990938US1




Figure 8

AUS990938US1

Page 1 of 2

I hereby declare that all statements made herein of my own knowledge are true and that all statements made on information and belief are believed to be true; and further that these statements were made with the knowledge that willful false statements and the like so made are punishable by fine or imprisonment, or both, under Section 1001 of Title 18 of the United States Code and that such willful false statements may jeopardize the validity of the application or any patent issued thereon.

POWER OF ATTORNEY: As a named inventor, I hereby appoint the following attorneys and/or agents to prosecute this application and transact all business in the Patent and Trademark Office connected therewith.

John W. Henderson, Jr., Reg. No. 26,907; Thomas E. Tyson, Reg. No. 28,543; James H. Barksdale, Jr., Reg. No. 24,091; Casimer K. Salys, Reg. No. 28,900; Robert M. Carwell, Reg. No. 28,499; Douglas H. Lefevre, Reg. No. 26,193; Jeffrey S. LaBaw, Reg. No. 31,633; David A. Mims, Jr., Reg. No. 32,708; Volel Emile, Reg. No. 39,969; Anthony V. England, Reg. No. 35,129; Leslie A. Van Leeuwen, Reg. No. 42,196; Christopher A. Hughes, Reg. No. 26,914; Edward A. Pennington, Reg. No. 32,588; John E. Hoel, Reg. No. 26,279; Joseph C. Redmond, Jr., Reg. No. 18,753; Marilyn S. Dawkins, Reg. No. 31,140; Mark E. McBurney, Reg. No. 33,114; Duke W. Yee, Reg. No. 34,285; Colin P. Cahoon, Reg. No. 38,836; Joseph R. Burwell, Reg. No. 44,468; Rudolph J. Buchel, Reg. No. 43,448; and Stephen R. Loe, Reg. No. 43,757, Stephen J. Walder, Reg. No. 41,534.

Send correspondence to: Duke W. Yee, Carstens, Yee & Cahoon, LLP, P.O. Box 802334, Dallas, Texas 75380 and direct all telephone calls to Duke W. Yee, (972) 367-2001

FULL NAME OF SOLE OR FIRST INVENTOR: RICHARD LOUIS ARNDT

INVENTORS SIGNATURE: Richard Louis Arndt DATE: 1 June 2000

RESIDENCE: 1607 BARN SWALLOW DRIVE  
AUSTIN, TEXAS 78746

CITIZENSHIP: UNITED STATES

POST OFFICE ADDRESS: SAME AS ABOVE